


Sheet title	
MAIN HOUSE FLOOR PLAN	
Drawn by	JP
Scale	SEE NOTES
Date	7-12-07
Checked by	JP
Project no.	07018



PLAN NOTES:

- | | |
|--|--|
| 1. PLAN NOTES | |
| <p>A COLUMN ABOVE</p> <p>B COLUMN BELOW</p> <p>C JOIST BEARING</p> <p>D JOIST OR BEAM HANGER</p> <p>E STEP IN PLAINFOOT OR CONC. SURFACE</p> <p>F [3'-6"]-2" STEP IN STEP ELEVATION</p> <p>G ALL COLUMNS SHALL BE 3'-2 1/2" DIA.</p> <p>H ALL BEARERS SHALL BE 3'-2 1/2" DIA. UNLESS
 OTHERWISE NOTED. ALL TRUSS MEMBERS SHALL BE 2'-0" DIA.</p> | <p>9. ALL EXT. WALLS ARE STEEL WALL PANELS & SHALL BE 1" THICKNESS. SEE STRUCT. FOR WALLS & FOUNDATION.</p> <p>10. FLOOR SHEADING SHALL BE 1" x 6" PLAINWOOD. CLASSED & NAILLED. SEE STRUCTURAL NOTES FOR NAILING INFO.</p> <p>11. SLOPED ROOF SHEADING SHALL BE 1" THICKNESS. CLASSED ROOF SHEADING SHALL BE 1" x 6" PLAINWOOD. SEE STRUCTURAL NOTES FOR NAILING INFO.</p> <p>12. ALL STEEL ROOF WELLS TO BE 10'-0" DIA. HORIZONTAL BEARING ON TRUSS. FLANGE W/ 3/8" x 2 1/2" x 24" O.C.</p> <p>13. ALL BEARING WALLS SHALL BE 2'-0" x 14" O.C. CLASD.</p> <p>14. ALL TRUSS BEAMS, COLUMNS & TRUSS MEMBERS SHALL BE W/ 1" THICK-FIR OR APPROVED EQUIT. LVLK</p> <p>15. ALL TRUSS BEAMS, COLUMNS & TRUSS MEMBERS SHALL BE 2'-0" DIA. UNLESS OTHERWISE NOTED. ALL TRUSS MEMBERS SHALL BE STANDARD DESIGN (CROSS) SPAN LUMBER.</p> |

Sheet title	
MAIN HOUSE FLOOR PLAN	
Drawn by	JP
Scale	SEE NOTES
Date	7-12-07
Checked by	JP
Project no.	07018